



When it comes to Safety always Travel the Extra Mile

Adjustment Limits for Clamp-Type Chambers with 621 kPa (90 psi) to 690 kPa (100 psi) Brake Application			
Size	Marking	Outside Diameter	Adjustment Limit
6	None	4 ½" (115mm)	1 ¼" (32mm)
9	None	5 ¼" (133mm)	1 ⅜" (35mm)
12	None	5 11/16" (144mm)	1 ⅜" (35mm)
16	None	6 ⅜" (162mm)	1 ¾" (45mm)
16L	L Stamped in Cover, Stroke Tag	6 ⅜" (162mm)	2" (51mm)
20	None	6 25/32" (172mm)	1 ¾" (45mm)
20L	L Stamped in Cover, Stroke Tag	6 25/32" (172mm)	2" (51mm)
24	None	7 7/32" (183mm)	1 ¾" (45mm)
24L	L Stamped in Cover, Stroke Tag	7 7/32" (183mm)	2" (51mm)
24LS	Square Ports, Tag & Cover Marking	7 7/32" (183mm)	2 ½" (64mm)
30	None	8 3/32" (205mm)	2" (51mm)
30	DD3 (Bus/Coach)	8 1/8" 206mm	2 ¼" (57mm)
30LS	Square Port, Tag & Cover Marking	8 3/32" (205mm)	2 ½" (64mm)
36	None	9" (228mm)	2 ¼" (57mm)